

comprising the steps of:

by a logging device, receiving a first notification when processing is started by the first data processing device, wherein the first notification includes input data entered when processing is started by the first data processing device;

generating process start time data using a clock of the logging device, wherein the process start time data includes time of receipt by the logging device of the first notification;

by the logging device, receiving a second notification when the processing is finished by the second data processing device, wherein the second notification includes at least part of the input data entered when processing is started by the first data processing device;

generating process end time data using the clock of the logging device, wherein the process end time data includes time of receipt by the logging device of the second notification;
and

calculating processing time by comparing the process start time data and the process end time data;

wherein, in the step of calculating, the process start time data and the process end time data are associated with each other using keywords of the input data entered when processing is started by the first data processing device.

14. (Amended twice) A data processing system comprising:

a first data processing device that starts processing;

a second data processing device for finishing processing; and

a logging device; wherein the logging device comprises:

logic for receiving a first notification including input data when processing is started by the first data processing device;

logic for generating process start time data using a clock of the logging device, wherein the process start time data includes time of receipt by the logging device of the first notification;

logic for receiving a second notification including at least part of the input data when processing is finished by the second data processing device;

logic for generating process end time data using the clock of the logging device, wherein the process end time data includes time of receipt by the logging device of the second notification; and

logic for associating the process start time data and the process end time data with each other using keywords of the input data, and calculating processing time by comparing the process start time data and the process end time data.

16. (Amended twice) A data logging system, comprising:

logic for receiving a first notification including input data when processing is started by a first data processing device;

logic for generating process start time data using a clock of the logging system, wherein the process start time data includes time of receipt by the logging system of the first notification;

logic for receiving a second notification including at least part of the input data when processing is finished by a second data processing device;

logic for generating process end time data using the clock of the logging system, wherein the process end time data includes time of receipt by the logging system of the second notification; and

logic for associating the process start time data and the process end time data with each other using keywords of the input data, and calculating processing time by comparing the process start time data and the process end time data.

17. (Amended twice) Programmable media containing programable software for measuring the performance of a data processing system wherein processing is started by a first data processing device and finished by a second data processing device which may have separate clocks that are not synchronized, the programmable software comprising the steps of:

receiving a first notification when processing is started by the first data processing device, wherein the first notification includes input data entered when processing is started by the first data processing device;

generating process start time data using a logging clock, wherein the process start time data includes time of receipt of the first notification;

receiving a second notification when the processing is finished by the second data processing device, wherein the second notification includes at least part of the input data entered when processing is started by the first data processing device;

generating process end time data using the logging clock, wherein the process end time data includes time of receipt of the second notification; and